# **Regulators**



## **PREST-O-LITE**<sup>®</sup> Pressure Regulators

- New and improved
- Small and lightweight, yet rugged and dependable
- Outperform regulators twice their size
- Oxygen models have patented, built-in Regulator Burnout (RBO) protection
- Fine mesh inlet filters prevent contamination



R-411/R-416 Regulator



R-522 Regulator

### **Specifications and Ordering Information**

### R-411/R-416

		Part	Maximum Delivery Pressure	Outlet	Gauges	
Gas	Model	Number	psig	Connection	Contents	<b>Delivery Pressure</b>
"B" Acetylene Tank (40 cf)	R-411B	04X36	15	"A" size	*	none
"MC" Acetylene Tank (10 cf)	R-411 MC	04X37	15	"A" size	*	none
Liquified Fuel Gas Cylinders with CGA 510 Outlet such as propylene or propane	R-416 LPG	05X38	60	"A" size	none	100 psig

### R-522

		Part	Maximum Delivery Pressure	
Gas	Model	Number	psig	CGA Outlet Connection
Oxygon	R-522-75-540	22237	75	9/16 in 18 RH male
Oxygen	R-522-75-540A	22554	75	3/8 in 24 RH male
Acetylene	R-522-15-520	22238	15	9/16 in 18 LH male
	R-522-15-200	22239	15	9/16 in 18 LH male
	R-522-15-300	22240	15	9/16 in 18 LH male
	R-522-15-510	22241	15	9/16 in 18 LH male
	R-522-15-510A	22555	15	3/8 in 24 LH male
Inert gas	R-522-CF-580	22492	10-40 cfh	5/8 in 18 RH female

\*Graduated as follows: full, 3/4, 1/2, 1/4, empty.

# **Regulators**



## **PREST-O-LITE**<sup>®</sup> Pressure Regulators

- New and improved
- Small and lightweight, yet rugged and dependable
- Outperform regulators twice their size
- Oxygen models have patented, built-in explosion protection
- Fine mesh inlet filters prevent contamination



R-22



R-36

## **Specifications and Ordering Information**

#### **R-22**

		Part	Maximum Delivery Pressure	Outlet	Gauges	
Gas	Model	Number	psig	Connection	Contents	<b>Delivery Pressure</b>
Acetylene						
"B" Acetylene Tank (40 cf)	R-22-15-520B	20971*	15	"B" size	***	15 psi
"MC" Acetylene Tank (10 cf)	R-22-15-200MC	20972**	15	"B" size	***	15 psi
Standard Acetylene Cylinders with CGA 510 Outlet	R-22-15-510A	998765	15	"A" size	4,00 psi	15 psi
Oxygen	· ·					
Standard Oxygen Cylinders with CGA 540 Outlet	R-22-75-540A	18564	75	"A" size	4,000 psi	100 psi

### **R-36**

		Part	Maximum Delivery Pressure	Outlet	Gauges	
Gas	Model	Number	psig	Connection	Contents	<b>Delivery Pressure</b>
Inert Gas	R-36-500-580	21365	500	1/4 flared 37°	4,000 psi	400 psi

\*20971 = 05X01 and 18Z56 Adapter.

\*\*20972 = 05X02 and 18Z56 Adapter.

\*\*\*Graduated as follows: full, 3/4, 1/2, 1/4, empty.