

**TWECO® FEMALE TERMINALS**

Stud Hole Size 17/32" (13,5mm)



(MODEL NO. / STOCK NO.)	Description	Accepts Male Ends	Standard Package
<b>1-AF-24</b> 9510-1102	45° Angle	1-MPC	24
<b>1-AF</b> 9510-1100	45° Angle	1-MPC	1
<b>1-OF-24</b> 9510-1103	180° Offset	1-MPC	24
<b>1-OF</b> 9510-1101	180° Offset	1-MPC	1
<b>2-AF-24</b> 9510-1112	45° Angle	2-MPC, 4-MPC	24
<b>2-AF</b> 9510-1110	45° Angle	2-MPC, 4-MPC	1
<b>2-OF-24</b> 9510-1113	180° Offset	2-MPC, 4-MPC	24
<b>2-OF</b> 9510-1111	180° Offset	2-MPC, 4-MPC	1

REPLACEMENT PARTS

Stock Number	Part Number	Description
9950-2100	<b>1-AF-11</b>	Insulated Cover - for 1-AF
9950-2101	<b>1-OF-11</b>	Insulated Cover - for 1-OF
9950-2102	<b>2-AF-11</b>	Insulated Cover - for 2-AF

Stock Number	Part Number	Description
9950-2103	<b>2-OF-11</b>	Insulated Cover - for 2-OF
9940-2125	<b>2-5</b>	Extra Cover Screws

**BALL-POINT CONNECTION TYPE LUGS**

Stud Hole Size 17/32" (13,5mm)



(MODEL NO. / STOCK NO.)	Description	Cable Capacity	Standard Package
<b>10-45-12</b> 9515-1104	45° Angle less insulated cover	thru 1/0	12
<b>10-45</b> 9515-1100	45° Angle less insulated cover	thru 1/0	1
<b>10-180-12</b> 9515-1105	180° Offset less insulated cover	thru 1/0	12
<b>10-180</b> 9515-1102	180° Offset less insulated cover	thru 1/0	1
<b>40-45-12</b> 9515-1106	45° Angle less insulated cover	thru 4/0	12
<b>40-45</b> 9515-1110	45° Angle less insulated cover	thru 4/0	1
<b>40-180-12</b> 9515-1107	180° Offset less insulated cover	thru 4/0	12
<b>40-180</b> 9515-1112	180° Offset less insulated cover	thru 4/0	1
<b>10-45C-12</b> 9515-1108	45° Angle with insulated cover	thru 1/0	12
<b>10-45C</b> 9515-1101	45° Angle with insulated cover	thru 1/0	1
<b>10-180C-12</b> 9515-1109	180° Offset with insulated cover	thru 1/0	12
<b>10-180C</b> 9515-1103	180° Offset with insulated cover	thru 1/0	1
<b>40-45C-12</b> 9515-1114	45° Angle with insulated cover	thru 4/0	12
<b>40-45C</b> 9515-1111	45° Angle with insulated cover	thru 4/0	1
<b>40-180C-12</b> 9515-1115	180° Offset with insulated cover	thru 4/0	12
<b>40-180C</b> 9515-1113	180° Offset with insulated cover	thru 4/0	1